

BUTTERFLY VALVE SERIES

蝶阀系列

设计标准: GB/T24925

尺寸: 1/2" 到 48" (DN15 到 DN1200)

压力: 150LB 到 2500LB 16公斤到420公斤

材质: 碳钢, 不锈钢, 其他

操作: 手柄, 蜗轮, 电动, 气动

特殊: 逸散性要求、抗H₂S介质要求、高性能蝶阀、凸耳球阀

Design Standard: GB/T 24925

Size: 1/2" to 48" (DN15 to DN1200)

Class: 150LB to 2500LB (16 bar to 420 bar)

Material: Carbon Steel, Stainless Steel, others

Operation: Lever, Gear, Electric, Pneumatic

Special: Fugitive Emission Valve, Re-H₂S Environment Valve,
High Performance Butterfly Valve, Lug Type Butterfly Valve



法兰硬密封蝶阀
Flange Metal
Seated Butterfly Valve

BUTTERFLY VALVE SERIES

蝶阀系列



高温三偏心对焊蝶阀
High Temperature
Triple Eccentric Butt Weld Butterfly Valve



大口径法兰硬密封蝶阀
Large Diameter Flange
Metal Seated Butterfly Valve



全焊接金属硬密封蝶阀
Fully Welded Metal Hard Seated
Butterfly Valve



双偏心蝶阀
Double Eccentric
Butterfly Valve



金属硬碰硬蝶阀
Large Diameter Flange
Metal Seated Butterfly Valve



对夹软密封蝶阀
Wafer Soft Seal
Butterfly Valve



送审稿

Tel:400-633-5118